

Technical Data

The Kinetico Premier Compact with e-max technology combines maximum performance and efficiency in a compact design - the ultimate in soft water convenience.



Specifications

Dimensions		
Size (w x d x h)	219 x 468 x 498 mm	
Shipping weight	15.6 kg	
Performance	HE	HF
Minimum Flow	0.25 l/min	1 l/min
Maximum Peak Flow	41 l/min	51 l/min
Regeneration		
Salt Used / Capacity	0.34 kg / 8 kg	0.34 kg / 8 kg
Time	11 minutes	11 minutes
Volume	20.5 litres	20.5 litres
System		
Media Volume	2 x 4.5 litres	2 x 4.5 litres
Inlet/Outlet Connections	¾" bsp male	¾" bsp male
Temperature Range	2 - 23°C	2 - 23°C
Operating Pressure (Min/Max)	1.8 - 6 bar	1.8 - 6 bar

Meter Disc	Type	1	2	3	4	5	6	7	8
Max hardness (in mg/L)	HE	57	120	173	241	309	379	448	507
	HF	63	125	186	246	305	362	419	474
Litres between regenerations	HE	2150	1075	717	537	430	358	307	269
	HF	1961	980	654	490	392	327	280	245

Features:



Kinetico's e-max technology balances optimum efficiency and maximum performance to give an unparalleled level of limescale prevention.



Precision engineered valve to operate quietly for minimum disturbance and noise level. It operates at particularly quiet levels while still delivering a consistently high performance.



Non-electric



Compact design



Metered Regeneration



10 year parts guarantee



Salt viewing window



Magnetic lid